Corona Sanding Sealer

GENERAL DESCRIPTI ON	CORONA Sanding Sealer penetrates and seals wood grain fibers for easy sanding. It enhances and warms the grain giving the look of natural wood. It is nitrocellulose based fast drying and bonding undercoat. Sanding Sealer can be used on plywood, furniture and bare timber work over new or previously finished surface.
PACK SIZE	0.91 Litre and 3.64 Litres
COLOUR RANGE	Clear
WATER RESISTANCE	Resistant to the levels of atmospheric humidity present in normal environment.
COMPOSITION (NOMINAL)	Pigment: Inert Filler Binder: Nitrocellulose Solvent: Volatile compounds BA, IPA
VOLUME SOLIDS	32± 2% (nominal)
FILM THICKNESS/COAT	Wet: 50 – 75 Micrometers Dry: 17 – 25 Micrometers
DRYING TIMES	Depends on temperature, humidity, air movements and film thickness
TOUCH DRY	15 –20 Minutes
RECOAT	1 – 1 ½ Hours
THEORETICAL	A guide to the theoretical coverage which can be achieved under normal
COVERAGE	conditions is 11 – 13m^2 /litre/coat.
APPLICATION:	Spray
THINNING	
CONVENTIONAL SPRAY	100 - 150% with CORONA Prime Thinner.
CLEANING UP	Clean all equipment with CORONA Prime Thinner immediately after use.
SURFACE PREPARATION	New, bare, old or previously painted surfaces must be clean, dry and free from wax, dust, rust and all unwanted material. Clean the surface by rubbing down with abrasive paper. Brush down previously painted surfaces and dust off. Apply CORONA Sanding Sealer on surfaces. Allow the Surface to dry, slightly rub down the surface with abrasive paper after each coat.
FLASH POINT	32°C
SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION	Highly inflammable. Keep container tightly closed, up right and out of reach of children. Keep away from the source of ignition e.g. cigarette, matchbox, lighter etc. Protect from extreme of temperature and store in a cool and dry place. Keep away from food, drink and animal feeding stuff. Keep container tightly closed. Wear suitable gloves, mask and safety goggles during application. Do not breathe in vapor and spray mist. May cause irritation to eyes, skin and respiratory system. Repeated exposure may cause skin dryness. Avoid contact with eyes and skin. In case of contact with eye rinse immediately with plenty of water and seek medical advice. If swallowed, rinse mouth with plenty of water (only if the person is conscious) show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire use foam, dry powder, CO2 fire extinguisher. Never use water. Take precautionary measure against static charges. Use only in well ventilated place. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose off paint waste in accordance with the appropriate environment quality regulation.

Surface Sealer

CORONA PAINTS