

## Corona Synthetic Clear Varnish

**GENERAL DESCRIPTION** 

CORONA Varnish has a high gloss finish and has excellent abrasion resistance. CORONA Varnish is a solvent-based varnish suitable for use on all type of new or previously treated wood and metal. Typical use includes paneling,

cane or wood furniture, windows, door and partitions.

PACK SIZE 0.25 Litre, 0.75 Liter and 3 Litres

**COLOUR RANGE** Clear

COMPOSITION (NOMINAL) Pigment: N/A

Binder: Alkyd

Solvent: Mineral Turpentine Oil

**VOLUME SOLIDS** 34± 2% (nominal)

FILM THICKNESS/COAT Wet: 50 - 75 Micrometers

Dry: 17 - 25 Micrometers

**DRYING TIMES**Depends on temperature, humidity, air movements and film thickness

TOUCH DRY 2-4 Hours

RECOAT 6-8 Hours

THEORETICAL A guide to the theoretical coverage which can be achieved under normal

**COVERAGE** conditions are 14 - 20m² /litre/coat

**APPLICATION:** Brush, Roller, or Spray

THINNING

BRUSH OR ROLLER: 10 - 20%

CONVENTIONAL SPRAY 30 - 40%

CLEANING UP Clean all equipment with mineral turpentine immediately after use.

Surface generally must be clean, dry and free from all defective or poorly adhering material, dirt, grease and wax etc. Previously painted surfaces should be thoroughly rubbed down using a suitable abrasive paper and then

dusted off.

FLASH POINT 33°C

SAFETY, HEALTH AND
ENVIRONMENTAL
INFORMATION

**SURFACE PREPARATION** 

Highly inflammable. Keep container tightly closed, up right and out of reach of children. Keep away from the source of ignition e.g cigarette, matchbox, lighter etc. Protect from extremes of temperatures and store in a cool and dry place. Keep away from food, drink and animal feeding stuff. Keep container tightly closed. Wear suitable gloves, mask and safety goggles during application. Do not breathe in vapor and spray mist. May cause irritation to eyes, skin and respiratory system. Repeated exposure may cause skin dryness. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, rinse mouth with plenty of water (only if the person is in conscious) show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire use foam, dry powder, CO<sub>2</sub> fire extinguisher. Never use water. Take precautionary measure against static charges. Use only in well ventilated place. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose

of any paint waste in accordance with the appropriate environmental quality regulation.

