Salts & Damp Resistant

Corona Elite Wall Primer

GENERAL DESCRIPTION	CORONA Wall Primer is a solvent-based sealer for interior masonry surface both new and previously painted surfaces, such as brickwork, plaster and cement. It reduces damage from alkali and salts also seals porous surface.
PACK SIZE	0.25 Litre, 0.91 Litre and 3.64 Litres
COLOUR RANGE	White Only
COMPOSITION (NOMINAL)	Pigment: Inert Filler Binder: Alkyd Resin Solvent: Mineral Turpentine Oil
VOLUME SOLIDS	50 ± 2% (nominal)
FILM THICKNESS/COAT	Wet: 75 - 100 Micrometers Dry: 34 - 46 Micrometers
DRYING TIMES	Depends on temperature, humidity, air movements and film thickness
TOUCH DRY	2 - 4 Hours
RECOAT	6 - 8 Hours
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 14.5 - 20m^2 /litre /coat.
APPLICATION:	Brush, Roller, Spray
THINNING	
BRUSH OR ROLLER	10 - 25%
CONVENTIONAL SPRAY	30 - 40%
CLEANING UP	Clean all equipment with Mineral turpentine immediately after use.
SURFACE PREPARATION	New or Previously Painted Surfaces must be clean, dry and free from grease, rust dust etc. Rub down the surfaces with the help of abrasive paper and remove previous paint. Clean with the help of cloth. Stir thoroughly before use.
FLASH POINT	34ºC
SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION	Highly inflammable. Keep container tightly closed, up right and out of reach of children. Keep away from the source of ignition e.g. cigarette, matchbox, lighter etc. Protect from extreme of temperature and store in a cool and dry place. Keep away from food, drink and animal feeding stuff. Keep container tightly closed. Wear suitable gloves, mask and safety goggles during application. Do not breathe in vapor and spray mist. May cause irritation to eyes, skin and respiratory system. Repeated exposure may cause skin dryness. Avoid contact with eyes and skin. In case of contact with eye rinse immediately with plenty of water and seek medical advice. If swallowed, rinse mouth with plenty of water (only if the person is conscious) show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire use foam, dry powder, CO2 fire extinguisher. Never use water. Take precautionary measure against static charges. Use only in well ventilated place. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose off paint waste in accordance with the appropriate environment quality regulation.

CORONA PAINTS