

Corona Elite Wall Putty

GENERAL DESCRIPTION

CORONA Elite Wall Putty is ideal for filling cracks, holes, gaps in plaster, wood and other building material. It forms an ideal base to give a durable, long lasting and smooth finish for CORONA Topcoats.

PACK SIZE 5kg and 20kg
COLOUR RANGE White Only

FILM PROPERTIES

WATER RESISTANCEResistant to the levels of atmospheric humidity present in normal environment.

COMPOSITION (NOMINAL) Pigment: Inert Filler

Binder: Acrylic Copolymer Emulsion.

Solvent: Water

VOLUME SOLIDS White $49 \pm 2\%$ (nominal) FILM THICKNESS/COAT Wet: 100- 150 Micrometers

Dry: 49-73 Micrometers

DRYING TIMESDepends on temperature, humidity, air movements and film thickness.

TOUCH DRY 2 - 3 Hours

RECOAT 4 - 6 Hours

THEORETICAL A guide to the theoretical coverage which can be achieved under normal

COVERAGE conditions is 6 - 10m²/kg/coat.

APPLICATION: Putty applicator

THINNING Ready to use

CLEANING UP Clean all equipment with water immediately after use.

SURFACE PREPARATION New, bare old or previously painted surfaces must be

New, bare old or previously painted surfaces must be clean, dry and free from dust or wax. Clean the surface by rubbing down with abrasive paper. Brush down previously painted surface completely and make the surface smooth. For large holes and cracks, use plaster of Paris or white cement. Allow it to dry. Apply CORONA Elite Aquas Wall Primer Sealer in order to seal the surface from water and salts. Allow surface to dry completely. Then

apply CORONA Elite Wall Putty.

FLASH POINT N/A

SAFETY, HEALTH AND
ENVIRONMENTAL
INFORMATION

Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contacts with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO_2 fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose off paint waste in accordance with appropriate environmental quality requirements. Any advice recommendations, information, assistance or service provided by Dawn Chemicals & Coatings Pvt. Ltd. in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed

or implied warranties.



