Spick & Span
Surfaces

Corona Interior Wall Putty

GENERAL DESCRIPTION	CORONA Interior Wall Putty (Sheesha) is a low VOC high quality Putty suitable for all types of interior masonry surface such as brick work, chipboard, hard board, plaster and cement etc. It gives more whiteness and coverage with excellent filling properties.
PACK SIZE	5.5 kg and 20kg
COLOUR RANGE	White Only
FILM PROPERTIES	
WATER RESISTANCE	Resistant to the levels of atmospheric humidity present in normal environment.
COMPOSITION (NOMINAL)	Pigment: Inert Filler Binder: PVA Copolymer Emulsion. Solvent: Water
VOLUME SOLIDS	White 46 ± 2% (nominal)
FILM THICKNESS/COAT	Wet: 100 - 125 Micrometers Dry: 46 - 57 Micrometers
DRYING TIMES	Depends on temperature, humidity, air movements and film thickness
TOUCH DRY	2 - 3 Hours
RECOAT	4 - 6 Hours
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 8-10m^2 /kg/coat.
APPLICATION:	Putty applicator
THINNING	Ready to use
CLEANING UP	Clean all equipment with water immediately after use.
SURFACE PREPARATION	New, bare old or previously painted surfaces must be clean, dry and free from dust or wax. Clean the surface by rubbing down with abrasive paper. Brush down previously painted surface completely and make the surface smooth. For large holes and cracks, use plaster of Paris or white cement. Allow it to dry. Apply CORONA Aquas Wall Primer Sealer in order to seal the surface from water and salts. Allow surface to dry completely. Then apply CORONA Interior Wall Putty (Sheesha).
FLASH POINT	N/A
SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION	Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contacts with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO_2 fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose off paint waste in accordance with appropriate environmental quality requirements. Any advice recommendations, information, assistance or service provided by Dawn Chemicals & Coatings Pvt. Ltd. in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.

CORONA PAINTS