

Corona Red Oxide Primer

GENERAL DESCRIPTION

PACK SIZE **COLOUR RANGE COMPOSITION (NOMINAL)** Pigment: Red Oxide

VOLUME SOLIDS FILM THICKNESS/COAT

DRYING TIMES TOUCH DRY RECOAT THEORETICAL COVERAGE **APPLICATION:** THINNING **BRUSH OR ROLLER: CONVENTIONAL SPRAY** 30 - 40% **CLEANING UP SURFACE PREPARATION**

FLASH POINT

SAFETY, HEALTH AND **ENVIRONMENTAL** INFORMATION

CORONA Red Oxide Primer is a solvent-based anti-corrosive protective primer for interior and exterior metal work including steelwork, iron etc. It is free from lead and heavy metals.

0.91 Litre, 3.64 Litres and 14.56 Litres

Red Only

Binder: Alkyd Resin Solvent: Mineral Turpentine Oil

48± 2% (nominal)

Wet: 50 - 75 Micrometers

Dry: 24 - 36 Micrometers

Depends on temperature, humidity, air movements and film thickness

2 - 4 Hours

6 - 8 Hours

A guide to the theoretical coverage which can be achieved under normal

conditions is 14 – 20m² /litre/coat.

Brush, Roller, Spray

10 - 25%

Clean all equipment with Mineral turpentine/Super Petrol immediately after use.

New or Previously Painted Surfaces must be clean, dry and free from grease, rust dust etc. Rub down the surfaces with the help of abrasive paper and remove previous paint. Clean with the help of cloth. Stir thoroughly before use.

33°C

Highly inflammable. Keep container tightly closed, up right and out of reach of children. Keep away from the source of ignition e.g. cigarette, matchbox, lighter etc. Protect from extreme of temperature and store in a cool and dry place. Keep away from food, drink and animal feeding stuff. Keep container tightly closed. Wear suitable gloves, mask and safety goggles during application. Do not breathe in vapor and spray mist. May cause irritation to eyes, skin and respiratory system. Repeated exposure may cause skin dryness. Avoid contact with eyes and skin. In case of contact with eye rinse immediately with plenty of water and seek medical advice. If swallowed, rinse mouth with plenty of water (only if the person is conscious) show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire use foam, dry powder, CO2 fire extinguisher. Never use water. Take precautionary measure against static charges. Use only in well ventilated place. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose off paint waste in accordance with the appropriate environment quality regulation.

