

Corona Sparkling Metallic Finish

GENERAL DESCRIPTION

CORONA Metallic Finish is a high-quality solvent-based metallic finish, suitable for use on all types of interior and exterior wood and metal surfaces. CORONA Metallic Finish Enamel gives a smooth metallic lustrous finish and has

excellent durability.

PACK SIZE 0.91 Litre and 3.64 Litrs

COLOUR RANGE See CORONA Metallic Finish shade card

COMPOSITION (NOMINAL) Pigment: Lightfast Pigments

Binder: Alkyd Resin
Solvent: Mineral Turnentine Oil

Solvent: Mineral Turpentine Oil

VOLUME SOLIDS 50± 2% (nominal)

FILM THICKNESS/COAT Wet: 50 - 75 Micrometers

Dry: 25 - 37 Micrometers

DRYING TIMESDepends on temperature, humidity, air movements and film thickness

TOUCH DRY 2-4 Hours

RECOAT 2-4 Hours

6-8 Hours

THEORETICAL A guide to the theoretical coverage which can be achieved under normal

COVERAGE conditions is $13.5 - 20 \text{m}^2 / \text{litre/coat}$

APPLICATION: Spray

THINNING

CONVENTIONAL SPRAY 20 - 25%

CLEANING UP Clean all equipment with Mineral turpentine/Super Petrol immediately after use.

SURFACE PREPARATION New, bare, old or previously painted surfaces must be clean, dry and free from wax, dust, rust and all unwanted

material. Clean the surface by rubbing down with abrasive paper. Brush down previously painted surfaces and dust off. Apply CORONA Red Oxide Primer on all metal surfaces in order to prevent from rust. Apply CORONA

Undercoat on all wood surfaces. Allow the Surfaces to dry completely. Stir thoroughly before use.

FLASH POINT 32°C

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION Highly inflammable. Keep container tightly closed, up right and out of reach of children. Keep away from the source of ignition e.g. cigarette, matchbox, lighter etc. Protect from extreme of temperature and store in a cool and dry place. Keep away from food, drink and animal feeding stuff. Keep container tightly closed. Wear suitable gloves, mask and safety goggles during application. Do not breathe in vapor and spray mist. May cause irritation to eyes, skin and respiratory system. Repeated exposure may cause skin dryness. Avoid contact with eyes and skin. In case of contact with eye rinse immediately with plenty of water and seek medical advice. If swallowed, rinse mouth with plenty of water (only if the person is conscious) show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire use foam, dry powder, CO₂ fire extinguisher. Never use water. Take precautionary measure against static charges. Use only in well ventilated place. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose

off paint waste in accordance with the appropriate environment quality regulation.

