

Corona Stain Free Matt Emulsion

Corona Stain Free Matt Emulsion is a Low VOC interior premium emulsion paint specially formulated to repel GENERAL DESCRIPTION

stains like ketchup, tea, coffee, juice, ink and hand prints etc. Stains can be removed without damaging the paint. It is a top-quality emulsion paint offering higher hiding and maximum protection on masonry surfaces including

brick work, plaster, cement and wall boards etc.

1Litre, 4 Litres and 16 Litres **PACK SIZE**

See Corona Stain Free Matt Emulsion shade card. **COLOUR RANGE**

FILM PROPERTIES

Resistant to the levels of atmospheric humidity present in normal environment. WATER RESISTANCE

COMPOSITION (NOMINAL) Pigment: Light fast Pigments

Binder: Acrylic Copolymer Emulsion.

Solvent: Water

White $28 \pm 2\%$ (nominal), other colors will vary. **VOLUME SOLIDS**

Wet: 75 - 100 Micrometers FILM THICKNESS/COAT

Dry: 21 - 28 Micrometers

Depends on temperature, humidity, air movements and film thickness **DRYING TIMES**

TOUCH DRY 2 - 3 Hours **RECOAT** 6 - 8 Hours THOROUGH DRY 72 hours

THEORETICAL A guide to the theoretical coverage which can be achieved under normal

conditions is 10-13m²/litre/coat. COVERAGE

APPLICATION: Brush or Roller

THINNING

10 - 25% **BRUSH OR ROLLER**

Clean all equipment with water immediately after use. **CLEANING UP**

SURFACE PREPARATION

New, bare, old or previously painted surfaces must be clean, dry and free from dust or wax. Clean the surface by rubbing down with abrasive paper. Brush down previously painted surface completely and make the surface smooth. For large holes and cracks, use plaster of Paris or white cement. Allow to dry. Rub down the surface with abrasive paper. Apply CORONA Aquas Wall Primer Sealer in order to seal the surface from water and salts and allow to dry. Apply CORONA Wall Putty Sheesha and allow to dry. Rub down the surface with abrasive paper and dust off. Now the surface will be smooth and ready for CORONA Stain Free Matt Emulsion to be applied. Stir the

paint thoroughly before use.

FLASH POINT N/A

SAFETY, HEALTH AND

Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contacts with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO₂ fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose off paint waste in accordance with appropriate environmental quality requirements.

Any advice recommendations, information, assistance or service provided by Dawn Chemicals & Coatings Pvt. Ltd. in relation to goods manufactured or marketed by it or their use or any applications is given in good faith



