

Corona Texture Finish

GENERAL DESCRIPTION

CORONA Texture Finish is a high-quality acrylic based waterborne texture paint which is used to produce different kinds of textural effects for interior/exterior masonry surfaces such as brickwork, plaster and concrete. It

can be over coated with a wide range of colors, which gives pleasing effects.

PACK SIZE 14.56 Litres White Only **COLOUR RANGE**

FILM PROPERTIES

WATER RESISTANCE Resistant to the levels of atmospheric humidity present in normal environment.

COMPOSITION (NOMINAL) Pigment: Inert Filler

Binder: Acrylic Copolymer Emulsion.

Solvent: Water

White $49 \pm 2\%$ (nominal) **VOLUME SOLIDS** Wet: 200 - 250 Micrometers FILM THICKNESS/COAT

Dry: 98 - 122 Micrometers

Depends on temperature, humidity, air movements and film thickness **DRYING TIMES**

TOUCH DRY 2 - 4 Hours RECOAT 4 – 8 Hours

A guide to the theoretical coverage which can be achieved under normal **THEORETICAL**

COVERAGE conditions are 4 - 5m²/kg/coat. **APPLICATION:** Texture Roller or Design Roller

THINNING Ready to use

Clean all equipment with water immediately after use. **CLEANING UP**

SURFACE PREPARATION

New, bare old or previously painted surfaces must be clean, dry and free from dust or wax. Clean the surface by rubbing down with abrasive paper. Brush down previously painted surface completely and make the surface smooth. For large holes and cracks, use plaster of Paris or white cement. Allow it to dry. For Interior Surfaces Apply CORONA Top Sealer Interior Primer in order to seal the surface from water and salts. Allow surface to dry completely. Apply CORONA Super Smooth Wall Filler and allow to dry. Apply CORONA Matt Finish and allow to dry. Now surface will be smooth and ready for CORONA Texture Finish to be applied.

Exterior For Exterior Applications, apply CORONA Aquas Wall Primer Sealer and allow to dry, Apply CORONA Wall Putty (Weather Barrier) and allow to dry. Apply CORONA Matt Finish and allow to dry. Now surface will be smooth and ready for CORONA Texture Finish to be applied.

FLASH POINT N/A

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION

Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contacts with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO₂ fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose off paint waste in accordance with appropriate environmental quality requirements.

Any advice recommendations, information, assistance or service provided by Dawn Chemicals & Coatings Pvt. Ltd. in relation to goods manufactured or marketed by it or their use or any applications is given in good faith





