

## Corona Top Sealer Interior Primer

**GENERAL DESCRIPTION** 

Top Sealer Interior Primer is a water-based wall sealer formulated to provide maximum protection against alkali and moisture, enhancing the performance of top coat. This interior primer is recommended for use on interior

plastered walls, ceilings, concrete, brickwork and wall boards, etc.

PACK SIZE 14.56 Litres

COLOUR RANGE White Only

FILM PROPERTIES

WATER RESISTANCE Resistant to the levels of atmospheric humidity present in normal environment.

COMPOSITION (NOMINAL) Pigment: Inert Fillers

Binder: PVA Copolymer Emulsion

Solvent: Water

**VOLUME SOLIDS** White  $39 \pm 2\%$ 

FILM THICKNESS/COAT Wet: 75-100 Micrometers

Dry: 30-40 Micrometers

**DRYING TIMES**Depends on temperature, humidity, air movements and film thickness

TOUCH DRY 2 - 4 Hours

RECOAT 4 - 6 Hours

THEORETICAL A guide to the theoretical coverage which can be achieved under normal

**COVERAGE** conditions is 11-13m<sup>2</sup>/litre/coat.

APPLICATION: Brush, Roller

THINNING

BRUSH OR ROLLER: 10 - 25%

CLEANING UP Clean all equipment with water after use.

rubbing down with abrasive paper. Brush down previously painted surface completely and make the surface smooth. For large holes and cracks, use plaster of Paris or white cement. Allow to dry. Rub down the surface with abrasive paper. Apply CORONA Top Sealer Interior Primer in order to seal the surface from water and salts and

New, bare, old or previously painted surfaces must be clean, dry and free from dust or wax. Clean the surface by

allow to dry.

FLASH POINT N/A

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION

**SURFACE PREPARATION** 

Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contacts with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO<sub>2</sub> fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose off paint waste in accordance with appropriate environmental quality requirements.

Any advice recommendations, information, assistance or service provided by Dawn Chemicals & Coatings Pvt. Ltd. in relation to goods manufactured or marketed by it or their use or any applications is given in good faith

without expressed or implied warranties.

Any advice recommendations, information, assistance or service provided by Dawn Chemicals & Coatings Pvt. Ltd. in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.



