

## Corona Undercoat

**GENERAL DESCRIPTION** 

CORONA Undercoat is excellent quality alkyd-based basecoat which gives maximum enamel hold out and provides smooth tough surface. It is highly recommended for use on the interior and exterior surfaces like wood

and metals. It is free from Lead and heavy metals.

PACK SIZE 0.91 Litre and 3.64 Litres

COLOUR RANGE White Only

COMPOSITION (NOMINAL) Pigment: Lightfast Pigments

Binder: Alkyd Resin

Solvent: Mineral Turpentine Oil

**VOLUME SOLIDS** 50± 2% (nominal)

FILM THICKNESS/COAT Wet: 50–75 Micrometers

Dry: 25-37 Micrometers

**DRYING TIMES**Depends on temperature, humidity, air movements and film thickness

TOUCH DRY 2 – 4 Hours

RECOAT 6 – 8 Hours

THEORETICAL A guide to the theoretical coverage which can be achieved under normal

**COVERAGE** conditions is  $14.5 - 20 \text{m}^2 / \text{litre/coat}$ .

APPLICATION: Brush, Roller, Spray

THINNING

BRUSH OR ROLLER: 10-25%

CONVENTIONAL SPRAY 30 - 40%

CLEANING UP Clean all equipment with Mineral turpentine/Super Petrol immediately after use.

SURFACE PREPARATION New or Previously Painted Surfaces must be clean, dry and free from grease, rust dust etc. Rub down the surfaces

use.

FLASH POINT 31°C

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION Highly inflammable. Keep container tightly closed, up right and out of reach of children. Keep away from the source of ignition e.g. cigarette, matchbox, lighter etc. Protect from extreme of temperature and store in a cool and dry place. Keep away from food, drink and animal feeding stuff. Keep container tightly closed. Wear suitable gloves, mask and safety goggles during application. Do not breathe in vapor and spray mist. May cause irritation to eyes, skin and respiratory system. Repeated exposure may cause skin dryness. Avoid contact with eyes and skin. In case of contact with eye rinse immediately with plenty of water and seek medical advice. If swallowed, rinse mouth with plenty of water (only if the person is conscious) show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire use foam, dry powder, CO<sub>2</sub> fire extinguisher. Never use water. Take precautionary measure against static charges. Use only in well ventilated place. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose

off paint waste in accordance with the appropriate environment quality regulation.

with the help of abrasive paper and remove previous paint. Clean with the help of cloth. Stir thoroughly before



